

24VDC/48W LED Driver

Feature:

1. Wide Voltage Input 85~264VAC
2. Protection: Short/Circuit/Over Voltage
3. 100% Full Load Test
4. Pass CE ROHS FCC
5. 1-Year Warranty



CE ROHS FCC

| | | | |
|--------------------------|----------------------------------------------|-----------------------|------------------|
| Input | | Over load | 105%-200% |
| Voltage range | 85~264VAC | Over voltage | 115%-135% |
| Frequency range | 47/63Hz | Environment | |
| Efficient | 80% | Working temp | -10~50°C |
| AC current(max) | 0.5A | Working humidity | 20%-90%RH |
| Peak load current | 40A/230V | Storage temp humidity | 20%-95%RH |
| Output | | Safety&EMC | |
| Voltage | 24VDC+/- 5% | Safety standard | CE ROHS FCC |
| Rated current | 2A | Withstand voltage | 5mA 2KVA |
| Rated power | 48W | Isolated resistance | 100M ohms |
| Ripple&noise | ≤100mV | Armor class | |
| Load regulations | ±1% | Others | |
| Setup.rise.hold up time. | 230V/500ms 20ms 30ms 115V/500ms 20ms 10ms | Dimension | 160mm*98mm *38mm |
| Protection | | Weight | 240g |
| Short circuit protection | | Localization | 162mm*100mm |

Typical Model List

| Model | Output Power | Output Voltage | Output Current | Tolerance |
|-------|--------------|----------------|----------------|-----------|
| 24V2A | 48W | 24 | 0~2A | ±5% |